



DPF Cleaner Foam

A cleaning agent for diesel particulate filters.



Features & Benefits

- Loosens carbon and ash deposits – aids diesel particulate filter regeneration
- Cleans without disassembling the DPF – easy application, saves time and money
- Outstanding foaming action – long penetration deep into the porous ceramic honeycomb body of the filter, high dissolving and cleaning power
- Convenient aerosol application – economical use, only one can is required per diesel particulate filter
- Use on all common diesel particle filter systems – universally applicable
- Reduces particulate matter emission – less environmental impact

P/N	Product	S/C	Packaging
86547	DPF Cleaner Foam	DPFF	500 ml aerosol & extension nozzle

Application

KENT DPF Cleaner Foam regenerates heavily soot contaminated diesel particulate filters and recovers the filter capacity to avoid loss of power or other problems because of a clogged DPF, caused by short distance driving.

In addition, it can be used as a cure at the first sign of a problem with the diesel particulate filter regeneration cycle. This is usually indicated by the illumination of a warning light.

The product will prevent the eventual serious fouling of the diesel particulate filter, which will result in expensive replacement and possible consequences in other parts of the combustion system – for example the turbo charger. KENT DPF Cleaner Foam will improve the efficiency of the vehicle.

Because of its easy application KENT DPF Cleaner Foam offers a quicker and in particular cheaper alternative to disassembling and cleaning a heavily soot contaminated diesel particulate filter at specialized external cleaning companies.

N.B.: Accompanying to the DPF cleaner Foam, KENT is offering the DPF Cleaner (P/N 86162) as an fuel additive to promote the diesel particulate filter regeneration.



Instructions

1. Allow the engine to cool down before using the product. The engine has to be cold and the DPF temperature below 40°C.
2. Disassemble the temperature or pressure sensor at the upper site of the diesel particle filter.
3. Shake the can before use and insert the extension nozzle in the opening with the spraying direction towards the filter.
4. Spray the product into the filter, in 3 to 5 sprays, with an interval of 5 minutes between each spray. Use the whole can.
5. Allow the product to soak for at least 30 minutes.
6. Reassemble the temperature or pressure sensor.
7. Start the engine and let it run idle. Dirty water contaminated with soot and ash will drip out of the exhaust pipe.
8. Allow the engine to run idle until the dripping stops.
9. Start the regeneration by performing a test drive for around 20 to 30 minutes at higher speed (approx. 60 mph or 100 km/h).

N.B.: If necessary, read the failure code and clear all codes.

Technical Information

Base:	Water based cleaner
Appearance / colour:	White foam
Odour:	Characteristic
Specific gravity (20 °C):	1.011 g/ml
pH-value (20 °C):	11
Dilution ratio:	Not applicable
Solubility in water:	Fully miscible
Application temp:	10 °C to 35 °C
Flash point:	- 97 °C
VOC:	264 g/l
Shelf life:	30 months
Custom tariff code:	3402 9010



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House,
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kenteurope.com

REV: 22/05/2017