

(GB)

Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.09.2016 / 0018
Replacing version dated / version: 29.02.2016 / 0017
Valid from: 12.09.2016
PDF print date: 12.09.2016
Black Magic S411
400 ml Art.: 6700 0048, Art.: 6704 0048

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Black Magic S411
400 ml Art.: 6700 0048, Art.: 6704 0048

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Corrosion protection
Rust remover
Sector of use [SU]:
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC24 - Lubricants, greases, release products

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

Theo Förch GmbH & Co. KG, Theo-Förch-Str. 11 - 15, 74196 Neuenstadt, Germany
Phone: 07139/95-0, Fax: 07139/95-199
info@foerch.de, www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.
STOT RE	1	H372-Causes damage to organs through prolonged or repeated exposure by inhalation.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.09.2016 / 0018

Replacing version dated / version: 29.02.2016 / 0017

Valid from: 12.09.2016

PDF print date: 12.09.2016

Black Magic S411

400 ml Art.: 6700 0048, Art.: 6704 0048


Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated. H372-Causes damage to organs through prolonged or repeated exposure by inhalation.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray.

P314-Get medical advice/attention if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH208-Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

White mineral oil (Natural oil)

Naphtha (petroleum), heavy alkylate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474878-16-XXXX
Index	649-482-00-X
EINECS, ELINCS, NLP	276-737-9
CAS	72623-86-0
content %	30-40
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Butane	
Registration number (REACH)	--
Index	601-004-00-0
EINECS, ELINCS, NLP	203-448-7
CAS	106-97-8
content %	20-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Gas 1, H220
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Registration number (REACH)	01-2119473977-17-XXXX
Index	---
EINECS, ELINCS, NLP	919-164-8 (REACH-IT List-No.)
CAS	(64742-82-1)

(GB)

Page 3 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

content %	10-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304 STOT RE 1, H372 (central nervous system) (as inhalation) Aquatic Chronic 3, H412

Propane	
Registration number (REACH)	--
Index	601-003-00-5
EINECS, ELINCS, NLP	200-827-9
CAS	74-98-6
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Gas 1, H220

Naphtha (petroleum), heavy alkylate	
Registration number (REACH)	--
Index	649-275-00-4
EINECS, ELINCS, NLP	265-067-2
CAS	64741-65-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413

Sulfonic acids, petroleum, calcium salts	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	263-093-9
CAS	61789-86-4
content %	0,01-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Consult doctor immediately - keep Data Sheet available.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Product removes fat.

Dermatitis (skin inflammation)

Skin irritation possible with prolonged contact.

Dizziness

Fatigue

Ingestion:

Danger of aspiration

Oedema of the lungs

(GB)

Page 4 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.09.2016 / 0018
Replacing version dated / version: 29.02.2016 / 0017
Valid from: 12.09.2016
PDF print date: 12.09.2016
Black Magic S411
400 ml Art.: 6700 0048, Art.: 6704 0048

Lung damage

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of explosion by prolonged heating.

Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Take precautions against electrostatic charges.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

GB

Page 5 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Observe special regulations for aerosols!
 Keep protected from direct sunlight and temperatures over 50°C.
 Observe special storage conditions.
 Store in a well ventilated place.
 Stability during storage:
 24 months.
 Classification of inflammability:
 C

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1000 mg/m³

Chemical Name	Butane	Content %:	20-30
WEL-TWA:	600 ppm (1450 mg/m ³)	WEL-STEL:	750 ppm (1810 mg/m ³)
Monitoring procedures:	- Compur - KITA-221 SA (549 459)		
BMGV:	---	Other information:	---
Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Content %:	10-30
WEL-TWA:	1000 mg/m ³	WEL-STEL:	---
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)		
BMGV:	---	Other information:	(WEL acc. to RCP-method, EH40)
Chemical Name	Propane	Content %:	1-10
WEL-TWA:	1000 ppm (ACGIH)	WEL-STEL:	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)		
BMGV:	---	Other information:	---
Chemical Name	Naphtha (petroleum), heavy alkylate	Content %:	1-5
WEL-TWA:	1200 mg/m ³ (>= C7 normal and branched chain alkanes)	WEL-STEL:	---
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)		
BMGV:	---	Other information:	---
Chemical Name	Graphite	Content %:	
WEL-TWA:	10 mg/m ³ (total inh. dust), 4 mg/m ³ (res. dust)	WEL-STEL:	---
Monitoring procedures:	---		
BMGV:	---	Other information:	---
Chemical Name	Oil mist, mineral	Content %:	
WEL-TWA:	5 mg/m ³ (ACGIH)	WEL-STEL:	10 mg/m ³ (ACGIH)
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)		
BMGV:	---	Other information:	---

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

(GB)

Page 6 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:
 With long-term contact:
 Protective nitrile gloves (EN 374)
 Minimum layer thickness in mm:
 0,9 - 1
 Permeation time (penetration time) in minutes:
 >= 480
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol, Active substance: Liquid
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined

(GB)

Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.09.2016 / 0018

Replacing version dated / version: 29.02.2016 / 0017

Valid from: 12.09.2016

PDF print date: 12.09.2016

Black Magic S411

400 ml Art.: 6700 0048, Art.: 6704 0048

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	2,9-3,5 bar (20°C)
Vapour pressure:	5,8-6,4 bar (50°C)
Vapour density (air = 1):	Not determined
Density:	~0,715 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not determined
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	20-50 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Black Magic S411

400 ml Art.: 6700 0048, Art.: 6704 0048

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.

(GB)

Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.09.2016 / 0018

Replacing version dated / version: 29.02.2016 / 0017

Valid from: 12.09.2016

PDF print date: 12.09.2016

Black Magic S411

400 ml Art.: 6700 0048, Art.: 6704 0048

Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/m ³ /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Aspiration hazard:						Yes
Symptoms:						nausea and vomiting.

Butane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>3400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>13,1	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion
Skin corrosion/irritation:						Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion

GB

Page 9 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Target organ(s): central nervous system
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, vomiting, annoyance, skin affections, heart/circulatory disorders, headaches, cramps, drowsiness, dizziness
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract).

Propane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Naphtha (petroleum), heavy alkylate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Aspiration hazard:						Yes
Symptoms:						drowsiness, headaches

Sulfonic acids, petroleum, calcium salts

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

GB

Page 10 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)

Graphite						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LC50	>2000	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	NOAEC	>2000	mg/m3/4h	Rat	OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Reproductive toxicity:	NOAEL	813	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Symptoms:						breathing difficulties

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Black Magic S411 400 ml Art.: 6700 0048, Art.: 6704 0048							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree (complexin g organic substance) >= 80%/28d: n.a.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

(GB)

Page 11 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	14d	>=1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l			
12.3. Bioaccumulative potential:							Readily biodegradable
Other information:	Log Pow		6,1				

Butane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	10-100	mg/l	Oncorhynchus mykiss		Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	10-22	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to daphnia:	NOELR	21d	0,28	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to daphnia:	LOEC/LOEL	21d	0,203	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchneriella subcapitata		Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	10-100	mg/l	Pseudokirchneriella subcapitata		Analogous conclusion
12.2. Persistence and degradability:		28d	74,7	%			Analogous conclusion

Propane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Sulfonic acids, petroleum, calcium salts

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Cyprinodon variegatus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		Analogous conclusion

(GB)

Page 12 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	8,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable

Graphite							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	IC50	72h	100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Water solubility:							Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

07 06 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Return to manufacturer with residual pressure.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

1950 Druckgaspackungen

Classification code: 5F

LQ (ADR 2015): 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1



(GB)

Page 13 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

14.4. Packing group: -
 EmS: F-D, S-U
 Marine Pollutant: n.a
 14.5. Environmental hazards: Not applicable

Transport by air (IATA)
 14.2. UN proper shipping name:
 Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.
 Observe restrictions:
 Observe youth employment law (German regulation).
 Comply with trade association/occupational health regulations.
 Observe law on protection of expectant mothers (German regulation).
 Directive 2010/75/EU (VOC): 57,88 %

REGULATION (EC) No 648/2004

30 % and more
 aliphatic hydrocarbons
 less than 5 %
 aromatic hydrocarbons

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.
 Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.
STOT RE 1, H372	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).
 H226 Flammable liquid and vapour.

Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.09.2016 / 0018

Replacing version dated / version: 29.02.2016 / 0017

Valid from: 12.09.2016

PDF print date: 12.09.2016

Black Magic S411

400 ml Art.: 6700 0048, Art.: 6704 0048

H372 Causes damage to organs through prolonged or repeated exposure by inhalation.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H220 Extremely flammable gas.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Aerosol — Aerosols

Asp. Tox. — Aspiration hazard

STOT RE — Specific target organ toxicity - repeated exposure

Flam. Gas — Flammable gases (including chemically unstable gases)

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Flam. Liq. — Flammable liquid

Skin Sens. — Skin sensitization

Förch France SAS
ZAE Marchais Renard/Aubigny
77950 Montereau-sur-le-Jard
FRANKREICH
Tel. +33 1 64144848
Fax +33 1 64144849
E-Mail info@forch.fr
Internet www.forch.fr

Förch SAS
17 rue de Marbourg
9764 MARNACH
LUXEMBURG
Tel. +352 269 03267
Fax +352 269 03368
E-Mail info@forch.fr
Internet www.forch.fr

Foerch S.R.L.
Str. Zizinului 110
500407 Brasov
RUMÄNIEN
Tel. +40 368 408192
Fax +40 368 408193
E-Mail info@foerch.ro
Internet www.foerch.ro

Förch A/S
Hagemannsvej 3
8600 SILKEBORG
DÄNEMARK
Tel. +45 86 823711
Fax +45 86 800617
E-Mail info@foerch.dk
Internet www.foerch.dk

Foerch AG
Netzibodenstrasse 23D
4133 Pratteln
SCHWEIZ
Tel. +41 61 8262030
Fax +41 61 8262039
E-Mail info@foerch.ch
Internet www.foerch.ch

Foerch BG
1225 Sofia, Bulgaria
22 Parva Balgarska Armia Bul., Office 2
Tel: 00359 2 981 2841
Fax: 00359 2 981 2841
info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
KROATIEN
Tel. +385 1 2912900
Fax +385 1 2912901
E-Mail info@foerch.hr
[internet www.foerch.hr](http://internet.www.foerch.hr)

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
ÖSTERREICH
Tel. +43 662 875574
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail info@foerch.at
Internet www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
SPANIEN
Tel. +34 958 40 17 76
Fax +34 958 40 17 87
E-Mail info@foerch.es
Internet www.foerch.es

Lhomme Tools & Fasteners
SEINHUISSTRAAT 5 B4
POORT 0331
3600 Genk
BELGIEN
Tel +32 89 71 66 61
Fax +32 89 71 59 27
E-Mail: info@lhomme-tools.be

Ziebe Limited
82 Westcott Venture Park
HP18 0XB Westcott, Aylesbury, Bucks
GROSSBRITANNIEN
Tel +44 12 96 65 52 82
Fax +44 12 96 65 19 47
E-Mail: sales-dept@ziebe.co.uk
Internet: www.ziebe.co.uk

Foermi Handelshaus LLC
Dimitrovskoe Autostrasse
Building 107/18
127247 Moscow
RUSSISCHE FOEDERATION
Tel. 7-495 657 99 57
Fax 7-495 485 87 98
E-Mail: foermi.moscow@foerch.ru
Internet: www.foerch.ru

Förch Polska Sp. z o.o.
43-392 MIĘDZYRZECZE GÓRNE 379
POLEN
k/ Bielska-Białej
Tel. +48 33 8157008
Fax +48 33 8157008
E-Mail info@forch.pl
Internet www.forch.pl

Vardalis & Co. EE.K.
62, ETHNIKIS ANTISTASIS STR.
57007 CHALKIDONA/THESSALONIKI
GRIECHENLAND
Tel +30 23 91 02 12 22
Fax +30 23 91 02 12 23
E-Mail: info@forch.gr
Internet: www.foerch.com

Förch Kereskedelmi Kft
Börgöndi út 14.
8000 Székesfehérvár
UNGARN
Tel. +36 22 348348
Fax +36 22 348355
info@foerch.hu
www.foerch.hu

Page 15 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.09.2016 / 0018
 Replacing version dated / version: 29.02.2016 / 0017
 Valid from: 12.09.2016
 PDF print date: 12.09.2016
 Black Magic S411
 400 ml Art.: 6700 0048, Art.: 6704 0048

Förch S.R.L.
 VIA GALVANI 40 C
 39100 BOLZANO
 ITALIEN
 Tel. +39 0471 204330
 Fax +39 0471 204290
 E-Mail info@forch.it
 Internet www.forch.it

Förch Nederland BV
 Zandbreeweg 12
 7577 BZ Oldenzaal
 NIEDERLANDE
 Tel. +31 541 751040
 Fax +31 541 751041
 E-Mail info@foerch.nl
 Internet www.foerch.nl

N1
 Dalvegur 10-14
 201 Kopavogur
 ISLAND
 Tel. +354 440 11 80
 Fax +354 440 10 10
 E-Mail: arni@n1.is
 Internet: www.n1.is

Förch Slovensko s.r.o.
 Rosinská cesta 12
 010 08 ŽILINA
 SLOWAKEI
 Tel +421 41 5002454
 Fax +421 41 5002455
 E-Mail info@forch.sk
 Internet www.forch.sk

Normteknik i Sverige AB
 Brännarevägen 1
 151 55 Södertälje
 SCHWEDEN
 Tel. +46 8 55 08 92 64
 Fax +46 8 55 08 90 62
 E-Mail: info@foerch.se
 Internet: www.foerch.se

Förch s.r.o.
 Dopravní 1/1314
 10400 PRAHA 10 – Uhřetěves
 TSCHECHIEN
 Tel. +420 271 001 984-9
 Fax +420 271 001 994-5
 E-Mail info@foerch.cz
 Internet www.foerch.cz

Förch d.o.o.
 LJUBLJANSKA CESTA 51A
 1236 TRZIN
 SLOWENIEN
 Tel. +38641825184
 Fax +38612442492
 E-Mail info@foerch.si
 Internet www.foerch.si

4SH AUSTRALIA PTY LTD.
 1/9 Vision Street
 6065 Wangara
 WESTERN AUSTRALIA
 Tel +61 8 93 03 91 13
 Fax +61 8 93 03 91 14
 E-Mail: sales@4sh.com.au
 Internet: www.foerch.com

Förch Portugal Lda
 Rua REPUBLICA DA BOLIVIA No. 69, 1 ESQ
 1500-544 Lisboa
 PORTUGAL
 Tel. +351 917314442
 Fax +351 253339576
 E-Mail info@forch.pt
 Internet www.forch.pt

Trigers SIA
 Straupes Street IEĻA 3
 1073 Riga
 LETTLAND
 Tel +371 6 7 90 25 15
 Fax +371 67 90 24 96
 E-Mail: trigers@trigers.lv
 Internet: www.trigers.lv

Förch Otomotiv Ltd. Şirketi
 HARAMIDERE MEVKII BEYSAN SAN.
 SITESI BIRLIK CAD. NO.6/2-3
 34520 Beylikdüzü/İstanbul
 Türkiye
 Tel. +90 (0)212 422 8744
 Fax +90 (0)212 422 8788
info@forch.com.tr

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service

Page 16 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.09.2016 / 0018
Replacing version dated / version: 29.02.2016 / 0017
Valid from: 12.09.2016
PDF print date: 12.09.2016
Black Magic S411
400 ml Art.: 6700 0048, Art.: 6704 0048

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic

Page 17 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.09.2016 / 0018
Replacing version dated / version: 29.02.2016 / 0017
Valid from: 12.09.2016
PDF print date: 12.09.2016
Black Magic S411
400 ml Art.: 6700 0048, Art.: 6704 0048

PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.